

Pulp - Task #4964

Task # 4961 (NEW): [Epic] Improve Integration and Testing with Nginx and Apache

Add variable to specify bind port for pulp-api and pulp-content-app

06/13/2019 08:51 PM - bmbouter

Status: MODIFIED	Start date:
Priority: Normal	Due date:
Assignee: bmbouter	% Done: 100%
Category:	Estimated time: 0:00 hour
Sprint/Milestone:	QA Contact:
Platform Release:	Complexity:
Blocks Release:	Smash Test:
Backwards Incompatible: No	Verified: No
Groomed: Yes	Verification Required: No
Sprint Candidate: Yes	Sprint: Sprint 54
Tags: Pulp 3 installer	
Description	
The user should be able to specify the bind string for both pulp-api and/or pulp-content-app.	
Related issues:	
Related to Pulp - Issue #4946: pulp_content_host default value is set in the ... MODIFIED	

Associated revisions

Revision 8eb135e6 - 06/18/2019 01:45 AM - bmbouter

Allow bind and nginx to be different

This introduces a pulp_api_bind variable in the 'pulp' playbook which the user can use to set the bind address (or multiple) of pulp-api. This is used by the pulp-api service template for the systemd service.

It moves the nginx and apache reverse proxy variables out of the 'pulp' playbook and into the 'pulp-webserver' playbook where they are used exclusively. The defaults are there also. It created 4 variables:

- pulp_content_host
- pulp_content_port
- pulp_api_host
- pulp_api_port

<https://pulp.plan.io/issues/4964>

closes #4964

History

#1 - 06/13/2019 08:52 PM - bmbouter

- Parent task set to #4961

#2 - 06/13/2019 09:43 PM - amacdona@redhat.com

- Related to Issue #4946: *pulp_content_host* default value is set in the wrong ansible role added

#3 - 06/13/2019 09:43 PM - amacdona@redhat.com

+1. Currently, we have:

pulp role:

pulp_api_host: localhost

pulp_api_port: 24817

pulp-content role:

pulp_content_host: 'localhost:24816'

pulp_content_bind: '0.0.0.0:24816'

I'm setting this to be related to <https://pulp.plan.io/issues/4946> which should be completed at the same time.

#4 - 06/13/2019 09:46 PM - mdepaulo@redhat.com

WRT the variables, they should be consistent across pulp-api & pulp-content.

Note that the *pulp_api_host* is used elsewhere in the ansible codebase, not just as the host to listen on. I think it gets advertised to clients.

So some refactoring should be done.

#5 - 06/14/2019 05:04 PM - amacdona@redhat.com

- Groomed changed from No to Yes

- Sprint Candidate changed from No to Yes

- Sprint set to Sprint 54

#6 - 06/17/2019 10:06 PM - bmbouter

- Status changed from NEW to ASSIGNED

- Assignee set to bmbouter

#7 - 06/18/2019 01:40 AM - bmbouter

- Status changed from ASSIGNED to POST

PR available at: <https://github.com/pulp/ansible-pulp/pull/123>

#8 - 06/18/2019 03:27 PM - bmbouter

- Status changed from POST to MODIFIED

- % Done changed from 0 to 100

Applied in changeset [ansible-pulp3|8eb135e627fb3be8c7bb3382305331000b83b569](https://pulp.plan.io/changeset/ansible-pulp3|8eb135e627fb3be8c7bb3382305331000b83b569).