

## RPM Support - Issue #5578

### rsync should use --skip-existing when creating remote directory

10/16/2019 05:51 PM - jluza

<b>Status:</b>	CLOSED - CURRENTRELEASE	<b>Start date:</b>	
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>		<b>Estimated time:</b>	0:00 hour
<b>Category:</b>			
<b>Sprint/Milestone:</b>			
<b>Severity:</b>	2. Medium	<b>Groomed:</b>	No
<b>Version:</b>		<b>Sprint Candidate:</b>	No
<b>Platform Release:</b>	2.21.1	<b>Tags:</b>	Pulp 2
<b>OS:</b>		<b>Sprint:</b>	Sprint 60
<b>Triaged:</b>	Yes	<b>Quarter:</b>	
<b>Description</b>			
When running rsync distributor remote_mkdir is used to create directory on remote. --skip-existing option should be added to arguments passed to the rsync command in order to avoid recreating existing directories			

#### Associated revisions

##### Revision e8b65799 - 10/16/2019 06:14 PM - jluza

Add --ignore-existing to remote\_mkdir (#3963)

- Add --ignore-existing to remote\_mkdir

To avoid recreating existing parts of directory structure --ignore-existing is added to arguments passed to rsync when calling remote\_mkdir

#### History

##### #1 - 10/16/2019 06:17 PM - ipanova@redhat.com

- Status changed from NEW to MODIFIED
- Triaged changed from No to Yes
- Sprint set to Sprint 60
- Tags Pulp 2 added

##### #2 - 10/16/2019 06:19 PM - ipanova@redhat.com

<https://github.com/pulp/pulp/pull/3963>

##### #3 - 01/22/2020 04:40 PM - ipanova@redhat.com

- Platform Release set to 2.21.1

##### #4 - 02/27/2020 05:38 PM - ipanova@redhat.com

- Status changed from MODIFIED to 5

##### #5 - 03/04/2020 05:46 PM - ipanova@redhat.com

- Status changed from 5 to CLOSED - CURRENTRELEASE