

RPM Support - Issue #717

Pulp-admin fails to publish rpm repo with serve-http and serve-https set false

03/01/2015 12:26 AM - marc@chadwick.net

| | | | |
|---|-------------------------|--------------------------|-----------|
| Status: | CLOSED - CURRENTRELEASE | Start date: | |
| Priority: | Normal | Due date: | |
| Assignee: | ipanova@redhat.com | Estimated time: | 0:00 hour |
| Category: | | | |
| Sprint/Milestone: | | | |
| Severity: | 2. Medium | Groomed: | No |
| Version: | 2.5 | Sprint Candidate: | No |
| Platform Release: | 2.7.0 | Tags: | Pulp 2 |
| OS: | | Sprint: | |
| Triaged: | Yes | Quarter: | |
| Description | | | |
| Log output | | | |
| Description of problem: | | | |
| If an rpm repository has both serve-http and serve-https set to false, and if at least one rpm in its contents, publish fails. Pulp-admin displays the following error: | | | |
| Task Failed | | | |
| coercing to Unicode: need string or buffer, NoneType found | | | |
| I am attaching a text file with the contents of ~/.pulp/server_calls.log. | | | |
| The publish succeeds if there is no content in the repo. | | | |
| Version-Release number of selected component (if applicable): | | | |
| pulp-admin-client-2.5.3-1.el6.noarch | | | |
| How reproducible: | | | |
| 100% | | | |
| Steps to Reproduce: | | | |
| 1. pulp-admin rpm repo create --repo-id foo --serve-http false --serve-https false | | | |
| 2. Upload or copy an RPM into this repo | | | |
| 3. pulp-admin rpm repo publish run --repo-id foo | | | |
| Actual results: | | | |
| Task Failed | | | |
| coercing to Unicode: need string or buffer, NoneType found | | | |
| Expected results: | | | |
| Publish should succeed and remove any previously published data. | | | |
| Additional info: | | | |
| Extra thanks to bcourt on IRC who helped track this down and asked that I open this bug | | | |
| + This bug was cloned from Bugzilla Bug #1196390 + | | | |

Associated revisions

Revision 23d9c093 - 06/30/2015 11:30 AM - ipanova@redhat.com

Adding validation that http and https cannot be set both to false.

With settings both set to false no publish will occur.

closes #717 <https://pulp.plan.io/issues/717>

History

#1 - 03/01/2015 12:26 AM - bcourt

This bug specifically kicks in when the incremental publish code is invoked and both serve-http and serve-https is set to false.

+ This comment was cloned from [Bugzilla #1196390 comment 1](#) +

#2 - 03/03/2015 05:15 PM - ipanova@redhat.com

- *Triaged* changed from *No* to *Yes*

- *Severity* set to *Medium*

#3 - 03/20/2015 08:15 PM - bmbouter

- *Severity* changed from *Medium* to *2. Medium*

#4 - 03/31/2015 06:35 PM - ipanova@redhat.com

- *Status* changed from *NEW* to *ASSIGNED*

- *Assignee* set to *ipanova@redhat.com*

#5 - 06/30/2015 11:34 AM - ipanova@redhat.com

- *Status* changed from *ASSIGNED* to *POST*

https://github.com/pulp/pulp_rpm/pull/703

#6 - 06/30/2015 05:44 PM - ipanova@redhat.com

- *Platform Release* set to *2.7.1*

#7 - 07/07/2015 05:53 PM - ipanova@redhat.com

- *Status* changed from *POST* to *MODIFIED*

- *% Done* changed from *0* to *100*

Applied in changeset [23d9c0934bac0cbf71f1083d8298e54b550a4179](#).

#8 - 12/10/2015 08:16 PM - amacdona@redhat.com

- *Platform Release* changed from *2.7.1* to *2.7.2*

#9 - 02/23/2016 09:57 PM - dkliban@redhat.com

- *Status* changed from *MODIFIED* to *5*

#10 - 05/27/2016 06:50 PM - semyers

- *Status* changed from *5* to *CLOSED - CURRENTRELEASE*

- *Platform Release* changed from *2.7.2* to *2.7.0*

#11 - 04/15/2019 11:05 PM - bmbouter

- *Tags Pulp 2* added

Files

3101cb398b6be649ae617009a245967d

2.27 KB

02/28/2015

marc@chadwick.net