

Pulp - Issue #7493

Installer: remove auth migration task

09/10/2020 11:44 PM - chouseknecht

Status:	CLOSED - CURRENTRELEASE	Start date:	
Priority:	Normal	Due date:	
Assignee:		Estimated time:	0:00 hour
Category:	Installer	Groomed:	No
Sprint/Milestone:	3.8.0	Sprint Candidate:	No
Severity:	3. High	Tags:	
Version:		Sprint:	
Platform Release:		Quarter:	
OS:			
Triaged:	No		

Description

Currently the installer runs auth migrations first, then runs all other migrations. This is causing the following error in galaxy_ng:

```
TASK [pulp_database_config : Run database auth migrations] *****
fatal: [pulp3-source-fedora31]: FAILED! => {
  "changed": true,
  "cmd": [
    "/usr/local/lib/pulp/bin/django-admin",
    "migrate",
    "auth",
    "--no-input"
  ],
  "delta": "0:00:04.244303",
  "end": "2020-09-10 20:49:05.957899",
  "rc": 1,
  "start": "2020-09-10 20:49:01.713596"
}
```

STDOUT:

Operations to perform:

Apply all migrations: auth

Running migrations:

```
Applying contenttypes.0001_initial... OK
Applying contenttypes.0002_remove_content_type_name... OK
Applying auth.0001_initial... OK
Applying auth.0002_alter_permission_name_max_length... OK
Applying auth.0003_alter_user_email_max_length... OK
Applying auth.0004_alter_user_username_opts... OK
Applying auth.0005_alter_user_last_login_null... OK
Applying auth.0006_require_contenttypes_0002... OK
Applying auth.0007_alter_validators_add_error_messages... OK
Applying auth.0008_alter_user_username_max_length... OK
Applying auth.0009_alter_user_last_name_max_length... OK
Applying auth.0010_alter_group_name_max_length... OK
Applying auth.0011_update_proxy_permissions... OK
```

STDERR:

Traceback (most recent call last):

```
File "/usr/local/lib/pulp/lib64/python3.7/site-packages/django/db/backends/utils.py", line 84, in
n_execute
    return self.cursor.execute(sql, params)
psycopg2.errors.UndefinedTable: relation "galaxy_user" does not exist
```

```
LINE 1: ...er"."is_active", "galaxy_user"."date_joined" FROM "galaxy_us...
```

Django's migration system should get it right (i.e., run things in the correct order) no matter what. If it isn't, it's because a dependency isn't in place correctly in the code that declares migration dependencies.

According to bmbouter, "Early on in pulp3 there was a requirement for it to be run in two-steps because we weren't committing migrations to git. Like years ago at this point. I think this is a vestige from that."

Related issues:

Related to Pulp - Issue #7499: pulp_installer is unpredictable about when it ...

CLOSED - CURRENTRELEASE

Associated revisions

Revision 0a0c3bbc - 09/14/2020 06:54 PM - chouseknecht

Allow auth migrations to work when installing galaxy_ng

fixes: #7493

Revision 0a0c3bbc - 09/14/2020 06:54 PM - chouseknecht

Allow auth migrations to work when installing galaxy_ng

fixes: #7493

Revision 187493e1 - 09/15/2020 02:11 PM - Mike DePaulo

Fix auth migrations being run for galaxy_ng.

Due to code removal, the pulp_default_admin_password is now set whenever pulpcore is 1st installed, updated/upgraded, or when pulp_upgraded_manually==true.

Also do 1 fix & 1 improvement for determining whether or not pulpcore was installed/upgraded.

We decided against modifying the auth migration task to not create the django-guardian anonymous user; a change in advertently introduced in 3.6.0. Doing so would have fixed migrations for galaxy_ng with fewer changes. However we want the anonymous user to get created, to help make Pulp installs consistent, whether pulp_installer 3.6.0 through 3.6.3 was run or whether future versions of it get run.

fixes: #7493

Revision 187493e1 - 09/15/2020 02:11 PM - Mike DePaulo

Fix auth migrations being run for galaxy_ng.

Due to code removal, the pulp_default_admin_password is now set whenever pulpcore is 1st installed, updated/upgraded, or when pulp_upgraded_manually==true.

Also do 1 fix & 1 improvement for determining whether or not pulpcore was installed/upgraded.

We decided against modifying the auth migration task to not create the django-guardian anonymous user; a change in advertently introduced in 3.6.0. Doing so would have fixed migrations for galaxy_ng with fewer changes. However we want the anonymous user to get created, to help make Pulp installs consistent, whether pulp_installer 3.6.0 through 3.6.3 was run or whether future versions of it get run.

fixes: #7493

History

#1 - 09/11/2020 10:02 PM - mdepaulo@redhat.com

- Related to Issue #7499: pulp_installer is unpredictable about when it resets the admin password added

#2 - 09/14/2020 11:35 AM - osapryki

The issue is caused by the [post migration hook](#) installed by the django-guardian package. The hook attempts to create an anonymous user. However since the user table is not a part of the django.contrib.auth application and is not available after applying auth migrations subset, the hook fails.

From django-guardian package code it appears that the post migration hook is controlled by the ANONYMOUS_USER_NAME settings parameter. If no ANONYMOUS_USER_NAME is set, it is set by default to AnonymousUser in [settings.py#L13](#).

As a workaround for this situation, creation of anonymous user can be disabled while applying auth migrations:

```
$ PULP_ANONYMOUS_USER_NAME='@none None' django-admin manage migrate --no-input auth
```

#3 - 09/14/2020 02:55 PM - rchan

https://github.com/pulp/pulp_installer/pull/427

#4 - 09/14/2020 07:53 PM - pulpbot

- Status changed from NEW to POST

PR: https://github.com/pulp/pulp_installer/pull/433

#5 - 09/15/2020 09:53 AM - chouseknecht

- Status changed from POST to MODIFIED

Applied in changeset [ansible-pulp|0a0c3bbc5ad904e0cc0d0532136a565fcd0f30d1](#).

#6 - 10/20/2020 05:48 PM - ttereshc

- Sprint/Milestone set to 3.8.0

#7 - 10/21/2020 04:49 PM - ttereshc

- Status changed from MODIFIED to CLOSED - CURRENTRELEASE