

Pulp - Task #8668

Add an example of how to specify an array value and a dict key using env vars

04/29/2021 10:58 PM - dannysauer

Status:	CLOSED - CURRENTRELEASE	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	100%
Category:		Estimated time:	0:00 hour
Sprint/Milestone:	3.13.0	Tags:	Documentation
Platform Release:		Sprint:	
Groomed:	No	Quarter:	
Sprint Candidate:	No		
Description			
The Pulp documentation lacks an example of using dynaconf's environment variable parsing to modify dictionaries, but makes reference to needing to change dictionaries in the config. This presents a minor hurdle for people who would like to run Pulp in something like Kubernetes where it's more common to put config in the container environment.			

Associated revisions

Revision 752ba8ca - 05/06/2021 12:08 PM - dannysauer

Add dynaconf nested value example

Add an example of how to specify an array value and a dict key in the auth methods section (which is particularly useful for people using k8s). Also expand/clarify a bit what the existing example is doing.

Fixes #8668

History

#1 - 04/29/2021 11:38 PM - pulpbot

- Status changed from NEW to POST

PR: <https://github.com/pulp/pulpcore/pull/1293>

#2 - 05/05/2021 05:44 PM - ipanova@redhat.com

- Tags Documentation added

#3 - 05/06/2021 12:08 PM - dannysauer

- Status changed from POST to MODIFIED

- % Done changed from 0 to 100

Applied in changeset [pulpcore|752ba8ca073abaa05a3dc42efbec6e5ca5c1e5de](https://github.com/pulp/pulpcore/pull/1293).

#4 - 05/25/2021 09:42 PM - dalley

- Sprint/Milestone set to 3.13.0

#5 - 05/26/2021 12:07 AM - pulpbot

- Status changed from MODIFIED to CLOSED - CURRENTRELEASE